

## Outdoor air conditioner



## Description

<b>Order Number:</b>	87622582
<b>Brand Name:</b>	COMPACT OUTDOOR
<b>Housing Material:</b>	Stainless steel AISI 304 (V2A)
<b>Ingress protection to EN 60 529:</b>	IP 56 / Type 12, 3, 3R, 4X
<b>Included:</b>	Mit Schaltschrankheizung und Aluminium Filter
<b>Approvals:</b>	CE, cURus, cULus

## Technical data

<b>Cooling capacity 95F/95F:</b>	6.0 kW @ 50 Hz
	6.2 kW @ 60 Hz
<b>Cooling capacity 95F/122F:</b>	4.8 kW @ 50 Hz
	5.4 kW @ 60 Hz
<b>Enclosure heater:</b>	2.0 kW
<b>Compressor type:</b>	Scroll Compressor
<b>Refrigerant / GWP:</b>	R134a / 1430
<b>Refrigerant charge:</b>	1140 g / 40.2 oz
<b>High / low pressure:</b>	32 / 6 bar
	460 / 88 psi
<b>Air volume flow (system / unimpeded):</b>	Ambient: 635 / 870 cfm
	Enclosure: 550 / 635 cfm
<b>Operating temperature range:</b>	-40°C - 55°C
<b>Mounting:</b>	Wall mounted
<b>Dimension H x W x D:</b>	44.7 x 17.9 x 15.4 inch
<b>Weight:</b>	85 kg
<b>Voltage / Frequency:</b>	380-415V 50 Hz 3~
	400-460 V 60 Hz 3~
<b>UL Voltage / Frequency:</b>	460 V - 60 Hz 3~
<b>Current 95F95F:</b>	5.9 A @ 50 Hz
	6.2 A @ 60 Hz
<b>Starting current:</b>	57 / 44 A
<b>Max. current:</b>	9.8 A
<b>Nominal power 95F95F:</b>	3.0 kW @ 50 Hz
	3.8 kW @ 60 Hz
<b>Max. power:</b>	6.3 kW
<b>Fuse:</b>	15 A (T)
<b>Max circuit ampacity:</b>	15 A
<b>Short-circuit current rating:</b>	5 kA
<b>Rated current compressor:</b>	6.4 A
<b>Full load current fans:</b>	1.3 A

**Connection:**

4 pole terminal block for power  
5 pole terminal block for signals,  
3 pole connector for RS 485 interface

---



## Order Information

<b>In Edelstahl 316 (V4A) Nr.</b>	87622584
<b>Verpackungsmaße</b>	1215 x 555 x 549.5 mm
<b>Bruttogewicht</b>	96.5 Kg
<b>Taric code</b>	84158200